Fugro Development Centre, 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong.
 Tel
 : +852 2450 8233

 Fax
 : +852 2450 6138

 E-mail
 : matlab@fugro.com

 Website
 : www.fugro.com



Page 1 of 1

Report no.: 183057CA196350

CALIBRATION CERTIFICATE OF SOUND LEVEL METER

Client Supplied Information

Client : Fugro Technical Services Ltd.

Address : Room 723 & 725, 7/F., Block B Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Chung, N.T. Project : Calibration Services

Details of Unit Under Test, UUT

Description	:	Sound Level Meter		
Manufacturer	:	Casella		
		Meter	Microphone	Preamplifier
Model No.	;	CEL-63X	CE-251	CEL-495
Serial No.	:	1488289	02789	004065
Next Calibration Date	:	23-Oct-2020		

Specification Limit : EN 61672: 2003 Type 1

Laboratory Information

Details of Reference Equipment -

Description:B & K Acoustic Multifunction Calibrator 4226 (Traditional free field setting)Equipment ID.:R-108-1Date of Calibration :24-Oct-2019Ambient Temperature : 22

Calibration Location : Calibration Laboratory of FTS

Method Used : By direct comparison

Calibration Results :

Parame	ters	Mean Value (dB)	Specific	Specification Limit(dB)			
	4000Hz	2.1	2.6	to	-0.6		
	2000Hz	1.6	2.8	to	-0.4		
	1000Hz	0.1	1.1	to	-1.1		
A-weighting	500Hz	-3.3	-1.8	to	-4.6		
frequency response	250Hz	-8.7	-7.2	to	-10.0		
response	125Hz	-16.2	-14.6	to	-17.6		
	63Hz	-26.2	-24.7	to	-27.7		
	31.5Hz	-38.9	-37.4	to	-41.4		
Differential level	94dB-104dB	0.0		± 0.6	3		
linearity	104dB-114dB	0.0		± 0.6	6		

Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. For calibration: Reference SPL are 94, 104 & 114dB, range setting is 20-140dB & time weighting is fast
- 4. The equipment does comply with EN 61672: 2003 Type 1 sound level meter for the above measurement.
- 5 The values given in this Calibration Certificate only relate to the values at the time of the test and any uncertainties will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during tranportation, overloading, mis-handling or the capability of any other laboratory to repeat the measurement.

Checked by :	William	Date : 1-11- 2019	_ Certified by : _	KT. Jour	Date :	1.11-2019
CA-R-297 (22/07/20)	09)		Leu	ng Kwok Tai (A	sistant Man	ager)
		** E	End of Report **	V		

Fugro Development Centre, 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong. Tel : +852 2450 8233 Fax : +852 2450 6138 E-mail : matlab@fugro.com Website : www.fugro.com



Page 1 of 1

Report no.: 183057CA196305

CALIBRATION CERTIFICATE OF SOUND LEVEL METER

Client Supplied Information

Client : Fugro Technical Services Ltd.

Address : Room 723 & 725, 7/F., Block B Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Chung, N.T. Project : Calibration Services

Details of Unit Under Test, UUT

Description Manufacturer	:	Sound Level Meter Casella		
Manalaotaro	0	Meter	Microphone	Preamplifier
Model No.	;	CEL-63X	CE-251	CEL-495
Serial No.	:	1488295	02809	003921
Next Calibration Date	÷	16-Oct-2020		

Specification Limit : EN 61672: 2003 Type 1

Laboratory Information

Details of Reference Equipment -

Description:B & K Acoustic Multifunction Calibrator 4226 (Traditional free field setting)Equipment ID.:R-108-1Date of Calibration :17-Oct-2019Ambient Temperature : 22

Calibration Location : Calibration Laboratory of FTS

Method Used : By direct comparison

Calibration Results :

Paramet		Mean Value (dB)	Specification Limit(dB)			
	4000Hz	1.4	2.6	to	-0.6	
	2000Hz	1.3	2.8	to	-0.4	
	1000Hz	0.0	1.1	to	-1.1	
A-weighting	500Hz	-3.4	-1.8	to	-4.6	
frequency response	250Hz	-8.7	-7.2	to	-10.0	
response	125Hz	-16.2	-14.6	to	-17.6	
	63Hz	-26.2	-24.7	to	-27.7	
	31.5Hz	-39.1	-37.4	to	-41.4	
Differential level	94dB-104dB	0.0		± 0.6	6	
linearity	104dB-114dB	0.0		± 0.6	3	

Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. For calibration: Reference SPL are 94, 104 & 114dB, range setting is 20-140dB & time weighting is fast
- 4. The equipment does comply with EN 61672: 2003 Type 1 sound level meter for the above measurement.
- 5 The values given in this Calibration Certificate only relate to the values at the time of the test and any uncertainties will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during tranportation, overloading, mis-handling or the capability of any other laboratory to repeat the measurement.

Checked by :	Alliam	Date :	23-10-2019				26-10-20	19
CA-R-297 (22/07/2009	9)			Leu	ng Kwok Tai (Assi	stant Man	ager)	
ananan sina malanda da 🤉 🖬 🗤 🦛 🦛 🥵 🥵			** E	nd of Report **				

This report shall not be reproduced except in full with prior written approval from the Company.

Fugro Development Centre, 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong. Tel : +852 2450 8233 Fax : +852 2450 6138 E-mail : matlab@fugro.com Website : www.fugro.com



Page 1 of 1

Report no.: 183057CA195873(1)

CALIBRATION CERTIFICATE OF SOUND CALIBRATOR

Client Supplied Information

Client : Fugro Technical Services Ltd.

Project : Calibration Services

Details of Unit Under Test, UUT

Description	:	Sound Calibrator
Manufacturer	:	Casella (Model CEL-120/1)
Serial No.	0	4358251
Equipment ID	3	N-34
Next Calibration Date	1	25-Jul-2020
Specification Limit	;	EN 60942: 2003 Type 1

Laboratory Information

Description	1	Reference Sound level	meter		
Equipment ID.	1	R-119-1			
Date of Calibrat	tion	: 26-Jul-2019	Ambient Temperature :	22	°C
Calibration Location : Calibration Laboratory of MateriaLab					
Method Used		By direct comparison			

Calibration Results :

Parameters (Setting of UUT)	Mean Value (error of measurement)	Specification Limit(dB)
94dB	-0.1 dB	
114dB	0.0 dB	±0.4dB

Remarks :

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. The equipment does comply with the specification limit.
- 4. The values given in this Calibration Certificate only relate to the values at the time of the test and any uncertainties will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during tranportation, overloading, mis-handling or the capability of any other laboratory to repeat the measurement.

Checked by : William	Date : 26-7-2019	Certified by :_	F.T. Loung	Date : 16-7-2019
CA-R-297 (22/07/2009)		Leung	Kwok Tai (Assista	ant Manager)

** End of Report **

This report shall not be reproduced except in full with prior written approval from the Company.

Fugro Development Centre, 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong. Tel : +852 2450 8233 Fax : +852 2450 6138 E-mail : matlab@fugro.com Website : www.fugro.com



Page 1 of 1

Report no.: 183057CA195873

CALIBRATION CERTIFICATE OF SOUND CALIBRATOR

Client Supplied Information

Client : Fugro Technical Services Ltd.

Project : Calibration Services

Details of Unit Under Test, UUT

Description	:	Sound Calibrator
Manufacturer	:	Casella (Model CEL-120/1)
Serial No.	:	4358289
Equipment ID	:	N-35
Next Calibration Date	:	25-Jul-2020
Specification Limit	1	EN 60942: 2003 Type 1

Laboratory Information

Description	:	Reference Sound level I	eference Sound level meter					
Equipment ID.	:	R-119-1						
Date of Calibrat	ion	: 26-Jul-2019	Ambient Temperature :	22	°C			
Calibration Loca	atior	n: Calibration Laborato	ry of FTS					
Method Used	:	By direct comparison						

Calibration Results :

Parameters (Setting of UUT)	Mean Value (error of measurement)	Specification Limit(dB)	
94dB	0.1 dB	±0.4dB	
114dB	0.0 dB	±0.40B	

Remarks :

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. The equipment does comply with the specification limit.
- 4. The values given in this Calibration Certificate only relate to the values at the time of the test and any uncertainties will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during tranportation, overloading, mis-handling or the capability of any other laboratory to repeat the measurement.

Checked by :	William	Date : 76-7-2019	Certified by :	RT Leung	Date : 76- 7	1-2019
CA-R-297 (22/07/2	009)	/	Leung	Kwok Tai (Assista	ant Manager)	

** End of Report **

This report shall not be reproduced except in full with prior written approval from the Company.



Calibration Certificate

0023157

Customer : Cinotech Consultants Limited RM 1710, Technology Park, 18 On Lai Street, Shatin, N.T. Hong Kong		Object 1 : Serial No. /Ref. No. : Object 2 : Serial No. /Ref. No. :	Microphone
Customer Code : SVEC09005		Manufacturer : BSV	VAtech
Date of calibration: Date of the recommended re-calibration:	08/01/2020 08/01/2021	Certificate No.: Handle by:	0023157 E0002

Measuring results

	Reference value	Indication value	Deviation	Allowed deviation	Object
Γ	94.0dB	94.2dB	+0.2dB	+/- 1.5dB	1
Γ	114.0dB	113.9dB	-0.1dB	+/- 1.5dB	1

Measuring equipment

index	Calibrator / Master	Traceability	
1	Master Sound Meter, SVAN949,sn:8571	IEC61672	
2 Sound Calibrator, SV30A sn:32580		IEC60942	

Ambient conditions

Temperature (20...26)°C

Humidity (20...60)%RH

Measuring procedure

Calibrated by Type 1 Sound Calibrator with Master Sound Level Meter under 1kHz Frequency.

Uncertainty

+/- 0.2 dB for probability not less than 95%.

Conformity

1. The resulted values were those obtained at the time of test and applies only to the item calibrated.

2. The measurement uncertainty was calculated according to the regulations of GUM with the coverage factor k=2 and contains

the uncertainty of the measuring procedure and the uncertainty of the measuring system.

3. The equipment being used in this calibration are regularly calibrated by laboratory according to ISO/IEC17025.

4.HKAS has accredited this laboratory (HOKLAS 267) for specific calibration activities as listed in the HOKLAS directory of accredited laboratories.

5. The calibrations certificate may not be reproduced.

Measured value(s) within the allowable deviation.	
Performed by	Approved by
Calibration Technician	Quality Manager

Appleone Calibration Laboratory Ltd. Rm1309, 13/F, No.77 Wing Hong St, Kln, HKSAR Tel: +852 2370 4437 Fax: +852 2114 0393

Equipment no.: N-12-02



Calibration Certificate

0022522

Customer		Object 1 : BSWA 308 SLM	
Cinotech Consultants Limited RM 1710, Technology Park,		Serial No. /Ref. No. : 570187 / 550841	
		Object 2 :	
18 On Lai Street, Shatin, N.T.		Serial No. /Ref. No.	
Hong Kong			
Customer Code : SVEC09005		Manufacturer : BSWAtech	
Date of calibration:	23/09/2019	Certificate No.: 0022522	
Date of the recommended re-calibration:	23/09/2020	Handle by: E0002	

Measuring results

	Reference value	Indication value	Deviation	Allowed deviation	Object
Γ	94.0dB	94.0dB	0.0dB	+/- 1.5dB	1
	114.0dB	113.9dB	-0.1dB	+/- 1.5dB	1

Measuring equipment

index	Calibrator / Master	Traceability
1	Master Sound Meter, SVAN949, sn:8571	IEC61672
2	Sound Calibrator, SV30A sn:32580	IEC60942

Ambient conditions

Temperature (20...26)°C

Humidity (20...60)%RH

Measuring procedure

Calibrated by Type 1 Sound Calibrator with Master Sound Level Meter under 1kHz Frequency.

Uncertainty

+/- 0.2 dB for probability not less than 95%.

Conformity

1. The resulted values were those obtained at the time of test and applies only to the item calibrated.

2. The measurement uncertainty was calculated according to the regulations of GUM with the coverage factor k=2 and contains

the uncertainty of the measuring procedure and the uncertainty of the measuring system.

3. The equipment being used in this calibration are regularly calibrated by laboratory according to ISO/IEC17025.

4.HKAS has accredited this laboratory (HOKLAS 267) for specific calibration activities as listed in the HOKLAS directory of accredited laboratories.

E The collinguities contificate as

5. The calibrations certificate may not be reproduced.	
Measured value(s) within the allowable deviation.	·
Performed by	Approved by
Calibration Technician	Quality Manager



Calibration Certificate

0022673

Customer : Cinotech Consultants Limited RM 1710, Technology Park, 18 On Lai Street, Shatin, N.T. Hong Kong		Object 1 : Serial No. /Ref. No. : Object 2 : Serial No. /Ref. No. :	ST-120 sound calibrator 181001608
Customer Code : SVEC09005		Manufacturer : Sou	ndtek
Date of calibration: Date of the recommended re-calibration:	24/10/2019 24/10/2020	Certificate No.: Handle by:	0022673 E0002

Measuring results

	Reference value	Indication value	Deviation	Allowed deviation	Object
Γ	94.0dB	94.0dB	0.0dB	+/- 0.3dB	1
Г	114.0dB	114.1dB	± 0.1 dB	+/- 0.5dB	1

Measuring equipment

index	Calibrator / Master	Traceability
1	Master Sound Meter, SVAN949, sn:8571	IEC61672
2	Sound Calibrator, SV30A sn:32580	IEC60942

Ambient conditions

Temperature (20...26)°C

Humidity (20...60)%RH

Measuring procedure

Calibrated by Type 1 Sound Level Meter and 1kHz Sound Source .

Uncertainty

+/- 0.2 dB for probability not less than 95%.

Conformity

1. The resulted values were those obtained at the time of test and applies only to the item calibrated.

2. The measurement uncertainty was calculated according to the regulations of GUM with the coverage factor k=2 and contains

the uncertainty of the measuring procedure and the uncertainty of the measuring system.

3. The equipment being used in this calibration are regularly calibrated by laboratory according to ISO/IEC17025.

4.HKAS has accredited this laboratory (HOKLAS 267) for specific calibration activities as listed in the HOKLAS directory of accredited laboratories.

5. The calibrations certificate may not be reproduced.

Measured value(s)	within	the allowable deviation.
-------------------	--------	--------------------------

Performed by

Calibration Technician

Approved by

Quality Manager



Calibration Certificate

0022675

Customer :		Object 1 :	ST-120 sound calibrator
Cinotech Consultants Limited		Serial No. /Ref. No. :	181001637
RM 1710, Technology Park,		Object 2 :	
18 On Lai Street, Shatin, N.T.		Serial No. /Ref. No. :	
Hong Kong			
Customer Code : SVEC09005		Manufacturer : Sour	ndtek
Date of calibration:	24/10/2019	Certificate No .:	0022675
Date of the recommended re-calibration:	24/10/2020	Handle by:	E0002

Measuring results

	Reference value	Indication value	Deviation	Allowed deviation	Object
Γ	94.0dB	94.0dB	0.0dB	+/- 0.3dB	1
Γ	114.0dB	114.0dB	0.0dB	+/- 0.5dB	1

Measuring equipment

index	Calibrator / Master	Traceability
1	Master Sound Meter, SVAN949, sn:8571	IEC61672
2	Sound Calibrator, SV30A sn:32580	IEC60942

Ambient conditions

Temperature (20...26)°C

Humidity (20...60)%RH

Measuring procedure

Calibrated by Type 1 Sound Level Meter and 1kHz Sound Source .

Uncertainty

+/- 0.2 dB for probability not less than 95%.

Conformity

1. The resulted values were those obtained at the time of test and applies only to the item calibrated.

2. The measurement uncertainty was calculated according to the regulations of GUM with the coverage factor k=2 and contains

the uncertainty of the measuring procedure and the uncertainty of the measuring system.

3. The equipment being used in this calibration are regularly calibrated by laboratory according to ISO/IEC17025.

4.HKAS has accredited this laboratory (HOKLAS 267) for specific calibration activities as listed in the HOKLAS directory of accredited laboratories

5. The calibrations certificate may not be reproduced.			
Measured value(s) within the allowa	ble deviation.		
Performed by	Approved by		
Calibration Technician	Quality Manager		